

Product Datasheet model ultrasonic 9302 600



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Model with reduced ventilation * Panoramic lens shape allows 180° uninterrupted lateral vision * Medium-energy impact 'B' (120 m/s) * Integrated, reduced ventilation allows air movement directly across the lens * Fits comfortably over most prescription spectacles * Simple lens replacement * High-quality, easily adjustable headband
<p>Technical details</p> <p>Frame</p> <p>Material</p> <p>Colour</p> <p>Material</p> <p>Features</p> <p>Colour</p>	<p>Front piece</p> <p>PP/TPE</p> <p>grey/blue</p> <p>Headband</p> <p>synthetic headband</p> <p>individually adjustable</p> <p>grey/black</p>

Lens	
Material	PC
Thickness	2,2 mm
Filter	2-1,2 according to DIN EN 170
Coating	supravisision HC-AF
Colour	clear
Optical class	1
Impact resistance	B (120 m/s) according to DIN EN 166
Miscellaneous	
Weight	80 g
Packing	4 goggles per box 72 pieces in one carton
Standards	DIN EN 166 + DIN EN 170