

The highly flexible ARION™ provides extreme levels of wearer comfort. The seal around the frame provides extra protection in dusty and dirty environments.

An individual fit can be achieved via the inclinable side-arms and the soft TPE components around the forehead, ears and nose help to maximise comfort.

SPECIAL FEATURES

- ✓ Single wide vision lens
- ✓ Soft TPE padded seal enhances comfort and protection
- ✓ Inclinable temple adjustment allows an easy fit onto most faces
- ✓ Co-injected bi-colour temples with flexible TPE ends enhance overall fit and comfort
- ✓ Optional head strap enhances the seal and fit
- ✓ Supplied with a microfibre storage pouch
- ✓ Weight: 35g
- ✓ 9-Base lens



TEMPFLEX



PANORAMIC VISION



PADDED SEAL



INCLINABLE TEMPLES



NO METAL
DIELECTRIC



CLEAR

GREY

VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	RLY00021	2C-1.2 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	TECTON K&N Anti-scratch and Anti-fog
GREY	RLY00022	5-2.5 e 1FTKN CE	e EN 166 FT CE	Impacts, UV and Solar radiations	
HEADSTRAP	RLYA0001	N/A	N/A	N/A	N/A

See overleaf for this product's technical specification →

GENERAL SPECIFICATION

LENS BASE	9mm
WEIGHT	35g

PACKAGING

Individually contained in a polythene bag with a Eurosot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	One piece, moulded
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	TR90 Thermoplastic/ Thermoplastic Elastomers (TPE)	Co-injected - Durable, flexible and lightweight
HINGE	TR90 Thermoplastic	Metal-free and durable

LENS MARKINGS

LENS FILTER TYPE:

2C UV

5 Solar

SCALE NUMBER (SHADE):

1.2 Clear or Amber

2.5 Grey

 Identity of the manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

T Protection against high-speed particles at extreme temperatures

PERFORMANCE:

K Resistance to scratches by fine particles

N Resistance to fogging

 Certification mark

FRAME MARKINGS

 Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

T Protection against high-speed particles at extreme temperatures

 Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

