



HPT FOAM PALM WITH HIGH RESISTANCE TO ABRASION

Durable and flexible PVC sponge touch coating using hydropellent technology provides excellent grip in oily, damp and dry handling conditions whilst maintaining good tactility.

FEATURES

- › PVC-HPT foam coating containing encapsulated air molecules provides an inherent cushioning effect
- › Tough, flexible PVC sponge touch finish coating using hydropellent technology provides a high level of grip and soaks up oil to help the hand to grip
- › Anatomically designed for comfort, dexterity and fit
- › Lint-free and silicone-free
- › Breathable back of glove to minimise perspiration
- › Seamless liner prevents irritation
- › Knitted wrist provides a secure fit
- › Sanitized® antimicrobial finish provides extra freshness



SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Engineering
- Food
- Logistics
- Manufacturing

Suitable Applications

- Assembly
- Light Engineering
- Packaging
- Precision Operations
- Warehousing

CERTIFICATION



See overleaf for explanation

**PRODUCTION INFORMATION**

MATERIALS	LINER:	13 gauge nylon
	COATING:	PVC HPT
COLOUR	Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SKY051	10 pairs per bag
8/M	SKY052	
9/L	SKY053	120 pairs per case
10/XL	SKY054	

CERTIFICATION LEGENDS**MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

ANSI/ISEA 105-2016 ABRASION RATING CHART

Abrasion Level Rating	0	1	2	3	4	5	6
Gram Load	500	500	500	500	1000	1000	1000
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000

ANSI/ISEA PUNCTURE RESISTANCE

ANSI Puncture Level	Puncture Resistance (newtons)
1	10-19
2	20-59
3	60-99
4	100-149
5	150+

Puncture Resistance (ANSI/ISEA 105): Puncture resistance is determined by the max force that it takes, exerted from a probe, to puncture the fabric.

GLOBUS**EUROPE**

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. (Notified Body No. 2777)