

58-530W Unique combination of grip and chemical resistance

Abrasion-resistant chemical gloves with heightened grip, perfect for indoor application

- Enhanced grip: AlphaTec[®] 58-530W chemical gloves' ANSELL GRIP[™] coating means less force is required when handling wet or oily components
- Elevated comfort: Their white nylon inner liner enhances comfort and offers excellent durability
- Advanced defenses: A bonded construction, whereby their coating polymer doesn't penetrate the liner in manufacture, guarantees EN 374 Type A chemical protection
- Improved durability: These AlphaTec[®] gloves also achieve EN level 3 and ANSI level 5 abrasion resistance levels
- Specialized protection: In addition, they offer EN 407 heat resistance, for improved workplace safety
- Augmented dexterity: AlphaTec[®] 58-530W industrial gloves' light 13-gauge design makes them more dexterous, for maneuverable hand protection

Industries

- Automotive
- Automotive Aftermarket
- Machinery and Equipment
- Metal fabrication
- Chemical
- Oil and gas

Applications

- Metalworking & assembly operations
- Body painting including surface
 inspection
 - Applying sealers, touching up
 - Changing tools and dies
 - Handling application & cleaning tools
 - Warehousing of raw materials
 - Loading and unloading trucks and vehicles
 - Filling, blending and charging of raw materials
 - Transferring liquids and solids
 - Loading and unloading of proces equipment
 - Transferring liquids and solids between vessels and tanks and process equipment
- Supervision of running operation
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Opening furnaces draining pumps valves or lines and crackers BTX process



Ansel

AlphaTe

58-530W Unique combination of grip and chemical resistance

Key Features

- ANSELL GRIP[™] Technology: Less force needed to grip wet or oily parts
- White nylon liner: Safety gloves with enhanced comfort and durability
- Bonded construction: Zero liner penetration, heightened dexterity •


Vulcanization Chemical Accelerators

• Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.



Performance Standards



Specifications

BRAND STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
AlphaTec [®] 58-530W	Nylon, Nitrile, ANSELL GRIP™	7, 8, 9, 10, 11	290 mm/ 11.4 inches	Grey	 6 pairs/polybag; 12 polybags/carton Vend pack variant ,1 pair per bag,72 bags per carton

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Ansell Healthcare Europ Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Canada Ansell Canada Inc. Ansell Canada Inc. 105, rue Lauder Cowansville (Québec) J2K 2K8, Canada T: 1 800 363-8340 F: 1 888 267-3551 North America Region Ansell Healthcare Products LLC

111 Wood Avenue South, Suite 210 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A de C.V Blvd. Bernardo Quintana No. 7001-C Blvd. Bernardo Quintana No. 70 Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2021 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.



Technologies