



PYRAMEX
Perform At Your Peak

PMXTREME® ANSI CE



RUBBER NOSEPIECE



INCLUDES STRAP



RUBBER TIPS

Built-in rubber nosepiece

Ventilated flexible temples with rubber temple tips

Includes black lanyard cord

Part No.	Black Frame with Cord	
ESB6310STP ●●	AF	Clear
ESB6320STP ●●	AF	Gray



PMXTREME® LED ANSI CE



RUBBER NOSEPIECE



RUBBER TIPS

Super bright swiveling LED bulbs (three lumens per side) allows you to see in dark places while keeping your hands free

Built-in rubber nosepiece and rubber temples tips

The alkaline batteries provide up to 50 hours of use before replacing. Three L44 alkaline batteries per temples (six total) are included

Easy to use push button on/off switches are located at the top of each temple

Part No.	Black Frame	
ESB6310STPLED ●●	AF	Clear



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) standards.

PMXTREME®

General Specifications

Weight: 27 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

Part No.	Lens Marking	Temple Marking
ESB6310STP	2 - 1.2 P 1 F K N CE	CE P EN166 F
ESB6320STP	5 - 3.1 P 1 F K N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Temple Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark

EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

PMXTREME LED

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

Part No.	Lens Marking	Temple Marking
ESB6310STPLED	2 - 1.2 P 1 F K N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Temple Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark

EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

