SKYTEC[®] **TEAL**[™]

SINGLE USE GLOVE, 100% NITRILE, POWDER FREE, 240MM LONG, 0.12MM THICK

Premium performance, powder-free, nitrile single use glove. Dual certified (Industrial and Medical), extremely strong and higher chemical and puncture resistance than regular nitrile disposables.

FEATURES

- > 100% premium quality nitrile
- > Palm thickness 0.12mm (5 mil)
- High resistance to penetration and projections of many chemicals
- Chlorinated inside to offer more comfort and reduce friction when donning
- > Powder-free, latex free, non-sterile, AQL 1.5
- > Approved for food handling
- > Dual labelling: PPE and medical
- Medical device compliant (MDD 93/42/EEC), conforms to EN455 (all parts)
- Antistatic properties due to inherent antistatic properties of nitrile



SUITABLE FOR


Typical Industries

- Chemicals
- Electronics
- Food
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Food Preparation
 Handling Oily
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
 Doint Spreyring
- Paint Spraying

CERTIFICATION



The second secon

See overleaf for explanation



SKYTEC° TEAL[™]

PRODUCT INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	-
COLOUR	Green	
LENGTH (mm)	240 mm	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING	VEND COMPA CODE	TIBLE OPTION PACKAGING
5½-6/XS 6½-7/S 7½-8/M 8½-9/L 9½-10/XL 10½ - 11/XXL	SKYTEAL0 SKYTEAL1 SKYTEAL2 SKYTEAL3 SKYTEAL4 SKYTEAL5	100 singles perbox 10 boxes percase	SKYVTEAL1 SKYVTEAL2 SKYVTEAL3 SKYVTEAL4	20 singles per box 50 boxes per case

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for thermal, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

Freedom from holes

Physical properties

Biological evaluation

CERTIFICATION LEGENDS

\sim		
--------	--	--

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE

М

Ν

0

S

CODE	CHEMICAL
A	Methanol
В	Acetone
С	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
Н	Tetrahydrofurane

ï

CHEMICAL n-Heptane Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid 99% Acetic acid 25% Ammonium hydroxide 30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehvde



GLOVES	TIME
A	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical

FOOD CONTACT

DIRECTIVE 2002 / 72 EC



EN455-1:

FN455-2:

EN455-3:



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

Ethyl acetate

VIRUS = Glove has passed ISO 16604: 2004 (method B)

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- **F:** +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- **T:** +971 4 882 9962
- F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2022 Globus (Shetland) Ltd | SKY-DATA-TEAL-0723_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777) The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.