

VELIA™ is a safety goggle containing a clear polycarbonate wraparound lens offering 180° field of vision.

The pivoting hand strap and soft, padded seal allows for a comfortable fit. An accompanying rubber strap can be used for cleanroom applications.

## SPECIAL FEATURES

- ✓ Wide field of vision
- ✓ Padded face seal
- ✓ Strong polycarbonate lens
- ✓ Soft PVC/TPE frame and comfort fit nose bridge
- ✓ Spare rubber strap for cleanroom use
- ✓ Quick release head strap buckle for ease of fitting when wearing a helmet
- ✓ Adjustable, pivoted elasticated head strap
- ✓ Molten metal splash protection
- ✓ Can be worn over a prescription frame
- ✓ Weight: 84g



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	○ RLY00221	2C-1.2 e 1BT9 CE	e EN 166 349BT CE	Impacts, Liquid Droplets, Molten Metal, Airborne Particles	Anti-fog
BUCKLE HEADSTRAP	RLYA0004	N/A	N/A	N/A	N/A

See overleaf for this product's technical specification

## GENERAL SPECIFICATION

LENS BASE	6mm
WEIGHT	84g

## PACKAGING

Individually contained in a polythene bag with a Eurosot

PER BOX	5
PER CARTON	100

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Single piece
FRAME	TR90 Thermoplastic / Thermoplastic Elastomers (TPE)	Durable, comfortable and lightweight
HEADBAND	Elastic or rubber	Adjustable with a cleanroom option
ATTACHMENT CLIPS/BUCKLE	TR90 Thermoplastic	Hard Wearing

## LENS MARKINGS

### LENS FILTER TYPE:

2C UV

### SCALE NUMBER (SHADE):

1.2 Clear or Amber

 Identity of the manufacturer

### OPTICAL CLASS:

1 High optical quality

### MECHANICAL STRENGTH:

- B** Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
- T** Protection against high-speed particles at extreme temperatures
- 9** Molten metal splash

 Certification mark

## FRAME MARKINGS

 Identity of the manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### FIELDS OF USE:

- 3** Liquid droplets or splashes
- 4** Large dust particles > 5 µm
- 9** Molten metal and hot solids

### MECHANICAL STRENGTH:

- B** Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
- T** Protection against high-speed particles at extreme temperatures

 Certification mark

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

## PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

[www.riley-eyewear.com](http://www.riley-eyewear.com)

E: [info@riley-eyewear.com](mailto:info@riley-eyewear.com)

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

