

Product Datasheet model pheos cx2 9198 257

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

**Product
characteristics**

- * Modern, sportive design with "x"-Brand
- * Comfortable protection due to directly injected forehead and nose pad
- * Innovative uvex duo component technology for maximum wearer comfort
- * Optimal protection due to twist temple technology for a perfect and non-slip fit
- * Duo spherical lens provides a perfect field of vision
- * Excellent ventilation ensures a well eye climate
- * A slim temple geometry enables the combination of the spec with other PPE (earmuffs, helmets and caps)

Technical details**Frame**

Material
Colour

Front piece/Temple

POM/TPE
blue, grey

Manufacturer's ID code
Applicable EN norm
Impact resistance
Resistance to high
speed particles at
extremes of temperat.
Conformity symbol

Marking

W
166
F (45 m/s)
T
CE

Lens

Material
Thickness
Coating
Colour

PC
2,2 mm
uvex supravison excellence
clear

Filter
Manufacturer's ID code
Optical class
Impact resistance
Resistance to high
speed particles at
extremes of temperat.
Surface resistance to
fine particles
Antifog
Conformity symbol

Marking

2C-1,2 (DIN EN 170)
W
1
F (45 m/s)
T
K
N
CE

Miscellaneous

Weight

28 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 170