



EXCEPTIONAL DURABILITY, BREATHABILITY AND FINGERTIP SENSITIVITY

The SHOWA 381 is designed to protect workers who switch between general handling and intricate assembly tasks. It contains a durable, lightweight microporous nitrile coating that delivers excellent levels of grip in dry and light oily conditions. The microfibre yarn liner quickly absorbs perspiration and moisture.

FEATURES

- › Constructed using a revolutionary 13 gauge SHOWA-engineered microfibre liner (0.52 denier)
- › Embossed nitrile palm finish disperses oil to increase grip and longevity in light oily environments
- › Microporous nitrile coating allows warm air and moisture from inside to escape
- › The 0.84mm finger thickness provides an excellent level of tactility and sensitivity
- › Microfibre yarn absorbs perspiration and moisture from the skin, resulting in drier and cooler hands
- › Exceptional suppleness, comfort and fit
- › A flexible glove designed for easy movement and extended wear
- › Protects from oils, grease and abrasion (8000 cycles)

LIGHTWEIGHT
13gg LINER



**VENDING
MACHINE
COMPATIBLE**



Capillary Action

The soft, microfibre liner absorbs perspiration in a way that's comparable to capillary action.

Moisture inside the glove flows into narrow spaces without the assistance of, and in opposition to external forces like gravity and evacuation. This is naturally triggered by heat emitted by the hand, causing natural vaporisation.



Embossed Microporous
Nitrile Palm Finish

SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Logistics
- Maintenance
- Manufacturing

Suitable Applications

- Assembly of Dry and Oily Parts
- General Handling
- Handling of Intricate Components
- Light Fabrication
- Mounting and Dismounting of Parts
- Tool Setting

CERTIFICATION

CAT II



EN 388:2016



4121X

See overleaf for explanation

**PRODUCT INFORMATION**

MATERIALS	LINER:	15 gauge polyester, microfibre, spandex
	COATING:	Foam nitrile
COLOUR	Black/grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE


- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/S	SHO3811	10 pairs per bag 120 pairs per case
7/M	SHO3812	
8/L	SHO3813	
9/XL	SHO3814	
10/XXL	SHO3815	

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

