

**Product Datasheet model pheos cx2 9198 237**

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

**Product  
characteristics**

- \* Modern, sportive design with “x”-Brand
- \* Comfortable protection due to directly injected forehead and nose pad
- \* Innovative uvex duo component technology for maximum wearer comfort
- \* Optimal protection due to twist temple technology for a perfect and non-slip fit
- \* Duo spherical lens provides a perfect field of vision
- \* Excellent ventilation ensures a well eye climate
- \* A slim temple geometry enables the combination of the spec with other PPE ( earmuffs, helmets and caps)

**Technical details****Frame**

Material  
Colour

**Front piece/Temple**

POM/TPE  
white, black

Manufacturer's ID code  
Applicable EN norm  
Impact resistance  
Resistance to high  
speed particles at  
extremes of temperat.  
Conformity symbol

**Marking**  
W  
166  
F (45 m/s)  
T  
CE

**Lens**

Material  
Thickness  
Coating  
Colour

PC  
2,2 mm  
uvex supravision excellence  
grey

Filter  
Manufacturer's ID code  
Optical class  
Impact resistance  
Resistance to high  
speed particles at  
extremes of temperat.  
Surface resistance to  
fine particles  
Antifog  
Conformity symbol

**Marking**  
5-2,5 (DIN EN 172)  
W  
1  
F (45 m/s)  
T  
K  
N  
CE

**Miscellaneous**

Weight

28 g

Packing

5 spectacles per box

Standards

160 spectacles per cardboard box

DIN EN 166 + DIN EN 172