

Neshoba™ is one of the lightest weight spectacles on the market, weighing in at 16 grams. To eliminate the threats of an eye injury, an employer should provide workers with products that are comfortable and dependable.





Neshoba™ ANSI CE CSA

Frameless design with thin flexible temples

Ultra lightweight spectacle – 16 gm

Part No.	Black Temples	
ES9710S • • •		Clear
ES9710ST • • •	AF	Clear H2X
ES9720S • • •		Gray
ES9720ST • • •	AF	Gray <mark>H2X</mark>
ES9730S • • •		Amber
ES9780S • • •		I/O Mirror
ES9780ST •	AF	I/O Mirror





Neshoba™

General Specifications

Weight: 16 gm PD: 64 mm Bridge: 12.3 mm Lens base: 9.5 curve

Lens size diagonal: 75.8 mm Lens size vertical: 43.3 mm Lens thickness: 1.6 mm

Overall length (lens - tip): 151 mm Overall width (hinge - hinge): 135 mm Closest point between temple tips: 78 mm Closest point between lens: 14.5 mm

Materials

Lens: polycarbonate Temples: polycarbonate Hinge: polycarbonate Screw: stainless steel

Part No.	Lens Markings	Frame Markings	
ES9710S	2 C - 1.2 P 1 F CE	CE P EN166 F	
ES9710ST	2 C - 1.2 P 1 F N CE	CE P EN166 F	
ES9720S	5 -2.5 P 1 F CE	CE P EN166 F	
ES9720ST	5 -2.5 P 1 F N CE	CE P EN166 F	
ES9730S	2 - 1.2 P 1 F CE	CE P EN166 F	
ES9780S	5 -1.7 P 1 F CE	CE P EN166 F	
ES9780ST	5 -1.7 P 1 F N CE	CE P EN166 F	

Lens Marking Symbols

Code - field of use

2 or 3: UV filter 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark N: Filter with anti-fog

CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard

P: Manufacturer's mark

EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at **PYRAMEXSAFETY.COM**