

SKYTEC Trigata™

LIGHTWEIGHT CUT RESISTANT POLYURETHANE COATED GLOVE

A palm-dipped, lightweight glove offering level B cut resistance (EN 388:2016). The thin PU coating allows a secure grip in dry and light oily handling conditions. Ideal for precision handling when protecting against cuts.

FEATURES

- › Cut resistant: Level B (EN 388:2016)
- › Palm-coated polyurethane
- › Lightweight 15 gauge liner
- › Secure grip in dry and light oily handling environments
- › Extremely hardwearing
- › Soft and breathable liner
- › Elasticated knitted wrist provides a secure and comfortable fit
- › Excellent dexterity
- › Sanitized® antimicrobial finish provides extra freshness



CUT LEVEL B

Sanitized Antifresh

LIGHTWEIGHT 15gg LINER

SUITABLE FOR

- | | |
|--|---|
| <p>Typical Industries</p> <ul style="list-style-type: none"> ▪ Aerospace ▪ Automotive ▪ Construction ▪ Engineering ▪ Glass ▪ Logistics ▪ Utilities | <p>Suitable Applications</p> <ul style="list-style-type: none"> ▪ Assembly ▪ Bottling/Canning ▪ Glass Manufacturing ▪ Handling of objects with sharp objects ▪ Maintenance ▪ Metal Fabrication ▪ Plastics Injection |
|--|---|

CERTIFICATION

CAT II	EN 388: 2016	ANSI/ISEA 105
	3X42B	
<i>See overleaf for explanation</i>		

**PRODUCTION INFORMATION**

MATERIALS	LINER:	15 gauge HPPE, glass fibre, nylon
	COATING:	Polyurethane (PU)
COLOUR	Blue	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKY900	10 pairs per bag
7/S	SKY901	
8/M	SKY902	120 pairs per case
9/L	SKY903	
10/XL	SKY904	
11/XXL	SKY905	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS**MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

GLOBUS**EUROPE**

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. (Notified Body No. 2777).

UKCA Type-Examination Certificate issued by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Approved Body No. 0321)