



PYRAMEX
Perform At Your Peak

Neshoba™ is one of the lightest weight spectacles on the market, weighing in at **16 grams**. To eliminate the threats of an eye injury, an employer should provide workers with products that are comfortable and dependable.



Neshoba™ ANSI CE CSA

Frameless design with thin flexible temples

Ultra lightweight spectacle – 16 gm

Part No.	Black Temples
ES9710S ●●●	Clear
ES9710ST ●●●	AF Clear H2X
ES9720S ●●●	Gray
ES9720ST ●●●	AF Gray H2X
ES9730S ●●●	Amber
ES9780S ●●●	I/O Mirror
ES9780ST ●	AF I/O Mirror



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) and Canadian (CSA Z94.3) (●) standards.

Neshoba™

General Specifications

Weight: 16 gm
 PD: 64 mm
 Bridge: 12.3 mm
 Lens base: 9.5 curve
 Lens size diagonal: 75.8 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.6 mm
 Overall length (lens - tip): 151 mm
 Overall width (hinge - hinge): 135 mm
 Closest point between temple tips: 78 mm
 Closest point between lens: 14.5 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
ES9710S	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9710ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ES9720S	5 -2.5 P 1 F CE	CE P EN166 F
ES9720ST	5 -2.5 P 1 F N CE	CE P EN166 F
ES9730S	2 - 1.2 P 1 F CE	CE P EN166 F
ES9780S	5 -1.7 P 1 F CE	CE P EN166 F
ES9780ST	5 -1.7 P 1 F N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com